Projector

mounts



It's great to have solutions...

PROJECTOR MOUNTS

Mounts any **brands** and

type of projector

With an Audipack projector mount, your projector is quickly and easily mounted to create a presentation solution. Audipack projector amounts are designed to precisely fit any brand or type of projector.

The interface makes it possible to swap projectors without the need to change the ceiling mount or lift. When necessary, switching the projector takes little time. Audipack designs and manufactures all mounts in- house and includes the manufacturers' recommendations in the product characteristics. The result is a perfect fit between mount and projector, ensuring the safest and most rigid product built.

	Ref.		
		QFIX-1	
	Max. mounting range in mm	440	20
-	max. load	10-20 kg	
the start of	Suitable for	Tube sets and products with ball-joint	
1	Ref.	QFIX-2	
1000 million (1000 million)	Max. mounting range in mm	440	Max. 20
	max. load	10-20 kg	
	Suitable for	Only for ceiling lifts	
	Ref.	QFIX-3	
Same	Max. mounting range in mm	100	Max.
1-	max. load	20-30 kg	30 O
-	Suitable for	all purposes	
Fix 4 & 5			
	Ref.	QFIX-4	
	Max. mounting range in mm	345 x 280	Max.
	max. load	30 kg	30
	Suitable for	large projector situations	(B)
L_			10
	Ref.	QFIX-5	
<i>a</i>	mounting range in mm	min. 268 x 243 - max. 430 x 360	Max.
	max. load	30 kg	30
	Suitable for	large projector situations	Ċ
RO- F IX 6 & 7			
	Ref.	QFIX-6	
	mounting range in mm	min. 200 x 85 - max. 410 x 475	Max. 80
11	max. load	80 kg	
10	Suitable for	large projector situations	i s
a'	Ref.	QFIX-7	
	Min - max mounting range in mm	200 x 85 - 620 - 735	Max.
*			
•	Max. load	80 kg	80

large projector situations

Suitable for

Ceiling mounts

for projectors



Features such as fast installation, easy adjustment and stability of any accessories are just as important.



Ultimate flexibility

with Audipack Ceiling mounts



Quatro-Fix®, the allrounder

The Quatro-Fix projector mounts offers maximum flexibility to set up any projector up to 20kg within the most complex of installs. The Quatro-Fix[®] ceiling mounts and the brand compatible mounts are equipped with a special newly designed ball joint that allows you to position the projector with minimal effort. The ball joint is designed to rotate from its own point of gravity. This results in a flexible and almost friction free adjustment capability.

UTS, for projector mounts and more.

Audipack also offers brand compatible projector mounts combined with the UTS (**U**niversal **T**ube **S**et) for any brand or type of projector, from stock. Brand compatible mounts are always a perfect fit and comply with manufacturers' installation guides and standards. For this type of ceiling mount an additional projector or camera mount is needed to complete the set.

UTS + brand related mount = the perfect solution





- Rigid and safe construction
- Any configuration possible
- Very flexible
- Integrated cable ducts



Angle adjustment



Perfect adjustment with telescopic feature





Cable passage



Cable passage

QUATRO-FIX



Max 20
Max
20 0
Max.
20 0
Max
20 0
Max

Angle adjustment in degrees 15° + 15°

QUATRO-FIX XL () 20 Kg. 30 kg 360 Mounting range in mm W336 x D 382 15° + 15°

Ref.	QFIX3-0100	
Length in mm	100	Max
Tube diameter in mm	54	30 0 0
Ref.	QFIX3-0300	
Length in mm	300	Max
Tube diameter in mm	54	30 0 0
Ref.	QFIX3-0500T	
Length in mm	355-500	Max
Tube diameter in mm	54-60	
Ref.	QFIX3-0700T	
Length in mm	450-700	Max
Tube diameter in mm	54-60	
Ref.	QFIX3-1000T	
Length in mm	604-1000	Max
Tube diameter in mm	54-60	

Angle adjustment in degrees

UNIVERSAL TUBE SET



Ref.	UTS-0100	
Length in mm	100	Max
Tube diameter in mm	54	30 0
Ref.	UTS-0300	
Length in mm	300	Max
Tube diameter in mm	54	30 0
Ref.	UTS-0500T	
Length in mm	355-500	Max
Tube diameter in mm	54-60	
Ref.	UTS-0700T	
Length in mm	450-700	Max
Tube diameter in mm	54-60	
Ref.	UTS-1000T	
Length in mm	604-1000	Max
Tube diameter in mm	54-60	

15° + 15° Angle adjustment in degrees

Quick Release,

the perfect **AV** solution ...

Look no further for a ceiling mount that allows the fast and easy exchange of projectors. The quick release ball joint allows swift and safe installation.





HEAVY DUT	Y PROJECTOR	CEILING	MOUNT
-----------	-------------	----------------	-------



Ref.	390065	
Length in mm	164	
Tube diameter in mm	45	Max.
Angle adjustment in degrees	20° + 20°	
Ref.	390061	
Length in mm	697-937	
Tube diameter in mm	45-50	Max.
Angle adjustment in degrees	20° + 20°	

QUICK RELEASE PROJECTOR CEILING MOUNT



Ref.	392165	
Length in mm	142	
Tube diameter in mm	45	Max.
Angle adjustment in degrees	30° + 30°	50
Ref.	392161	
Length in mm	675-915	
Tube diameter in mm	45-50	Max

30° + 30°

50

Angle adjustment in degrees



The **heavy duty** universal ceiling mount is a TüV certified rigid and strong ceiling mount suited for suspending projectors up to 70 kg from the ceiling. The ceiling mount is standard equipped with the patented Audipack ball-joint, which features the unique possibility **to line out** the projector to the projection screen. De cable-outlets enable a neat and safe installation of all the necessary connections.



The **Quick Release** ceiling mounts are ergonomic solutions especially designed for rental and stage use. The special releasable ball joint allows the projector up to 50 kg to be **installed quickly without any tools**. The ingenious construction releases the ball joint adjustment and makes swapping and positioning the projector easy.



The **Quick Release Plus** projector ceiling mounts are ergonomic solutions designed for rental and stage use. The special releasable ball joint allows the projector up to 50 kg to be **installed quickly without any tools**. The ingenious construction releases the ball joint adjustment and makes swapping and positioning the projector easy.

The Plus version has an additional adjustment platform with **3 adjustment knobs**, with which the projector position can be adjusted highly accurate. Ideal for those who use more than 1 projector in one and the same set up!

QUICK RELEASE PLUS PROJECTOR CEILING MOUNT WITH 3D ADJUSTMENT



Ref.	392365	
Length in mm	193	
Tube diameter in mm	45	Max.
Angle adjustment in degrees	30° + 30°	50
Fine tune adjustment in degrees	-3°, +3°	
Ref.	392361	
Length in mm	726-966	
Tube diameter in mm	45-50	Max.
Angle adjustment in degrees	30° + 30°	
Fine tune adjustment in degrees	-3°, +3°	

QUICK RELEASE PLUS + TRUSS MOUNT WITH 3D ADJUSTMENT & HORIZONTAL SHIFT



303	
30° + 30°	Max
-3°, +3°	50
40	
392666	
740 - 900	
30° + 30°	Max.
-3°, +3°	50
40	
392665	
740 - 900	
30° + 30°	Max
-3°, +3°	50
40	
	30° + 30° -3°, +3° 40 392666 740 - 900 30° + 30° -3°, +3° 40 392665 740 - 900 30° + 30° -3°, +3°

Projector mount

for **vertical** positioning



An elegant and rigid solution for installing projectors to the ceiling, with the minimalistic design well known from the 800 series product line.

This mount is specially designed for projectors with a special lens that allow a vertical installation.

The ceiling mount is equipped with features to line out the projector to the projection screen. De cable management system in the tube enables a neat and safe installation of all the necessary connections.

The mounting interface has a square 90 mm pattern on which the projector can be mounted. This is possible with the 392618 cams, which are included with the projecto ceiling mounts.

- Slim and minimalistic design
- Easy cable management
- Available in many sizes
- Adjustable in heigth

Ceiling mount for vertical projection



Ref.
Length in mm
Tube
Angle adjustment in degrees
Mounting interface

PCM-800-1000

1000 800 series with cable management -3° + 7° L&S 4 - square pattern 90 mm



Ref. Length in mm Tube

Angle adjustment in degrees Mounting interface

PCM-800-XXXX

custom 800 series with cable management -3° + 7° L&S 4 - square pattern 90 mm





PROJECTOR MOUNTS

Mount any brand and type of projector on any Audipack system with the Audipack system with the Audipack projectors, brand related models are available.
Image: Constraint of the Audipack system with the Audipack projectors, brand related models are available.
Image: Constraint of the Audipack system with the Audipack projectors, brand related models are available.
Image: Constraint of the Audipack system with the Audi



EQUIPMENT CABINET	
	For above ceiling installation
Ref. Max. equipment dimensions in mm	EC-5 W 350 x D 350 x H 100



Ref. Suitable for **392193** 390065, 390061, 392165, 392161, 392365, 392361, 392665, 392661





Several Options



Binopungentert <

Truss mounts

for projectors

Audipack truss mounts, ideal for rental & staging

Audipack truss mounts offer flexible installation options and secure features

TRUSS MOUNTS

Safe and solid

truss mounting



Fine pitch, pixel on pixel adjustment

Rigid and safe construction

Any configuration possible

Integrated cable ducts

Very flexible

Do you need easy and quick projector truss mounting? Use the Audipack truss mounts!

Audipack offers a wide range of truss mountable projector mounts and solutions. To address different applications, Audipack offers specific solutions, from a simple projector mount to sophisticated 3D adjustment features. The mounts allow a quick and safe installation to be performed every time.

The UTC range offers a universal but very flexible and well-designed mounting range for projectors up to 30kg. Light weight, tolerance free and with integrated ball joints for perfect screen alignment.

The Quick release product line is distinguished by its unique separable ball joint and is the safest way for installing projectors up to 52kg to trusses. After installing the tube set, just click the projector to the tube set - 'click and go'.

Align the projector to the screen with the ball joint or even with the optional 3D adjustment (QR-plus) or linear adjustment (QR-plus+); ideal for seamless projection.

Quick release, the perfect AV rental solution ...

Look no further for a ceiling mount that allows the fast and easy exchange of projectors. The quick release ball joint allows swift and safe installation. Especially designed for professional rental and stage use.





Perfect adjustment with telescopic feature



399941 Stainless steel security cable

Cable passage



Cable passage

Truss mounts

TRUSS MOUNTS WITH STANDARD BALL JOINT



Ref.	UTC-0150B	
Length in mm	150	
Angle adjustment in degrees	15° + 15°	Max. 30
Ref.	UTC-0300B	
Length in mm	300	
Angle adjustment in degrees	15° + 15°	Max. 30
Ref.	UTC-1000TB	
Length in mm	604-1000	
Angle adjustment in degrees	15° + 15°	Max. 30

QUICK RELEASE TRUSS MOUNT



Ref.	392167	
Length in mm	252	
Angle adjustment in degrees	30° + 30°	Max. 50
Ref.	392166	
Ref. Length in mm	392166 760-1000	

Ref.	392367	
Length in mm	303	
Angle adjustment in degrees	30° + 30°	Max.
Fine tune adjustment in degrees	-3°, +3°	
Ref.	392366	
Ref. Length in mm	392366 811-1051	
Y		Max 50

TRUSS MOUNTS





EXTENSION TUBES (SUITABLE FOR THE UTC)



EXTENSION TUBES (ONLY SUITABLE FOR QUICK RELEASE TUBE SETS)





The BJ-PRO Ball-joints are heavy duty mounting solutions for installing projectors or equipment temporarily to trusses.

With the adjustable ball-joint the aiming direction of the projector can be adjusted and with the micro adjustment the projector can be aligned to the screen.

Installing the projector is easy, no tools needed! With the preinstalled Audipack bracket to the projector, the projector is installed and removed with the quick-release "1/4 turn&lock" to the ball joint.

Safely store all your items in an Audipack flightcase.



BJ-PRO PROJECTOR TRUSS MOUNT

	ġ.	*
1	20	<u>II</u>
	-	

Ref.	BJ-PRO-BASIC single truss	hook
Height in mm	330	
Angle adjustment in degrees	25°/ 0° / 25°	Max. 200
Truss - diameter	50 mm	200
Ref.	BJ-PRO-1 single truss hook	
Height in mm	330	
Angle adjustment in degrees	25°/ 0° / 25°	Max. 200
Fine tune adjustment in degrees	5° / 0° / 5°	
Truss - diameter	50 mm	
Ref.	BJ-PRO-2 double truss hook	<u>۲</u>
Height in mm	330	
Angle adjustment in degrees	25°/ 0° / 25°	Max. 200
	5° / 0° / 5°	
Fine tune adjustment in degrees		

Truss mounts

BJ-PRO PROJECTOR TRUSS MOUNT

Ref.

Ref.

Mounting interface

Mounting interface

Suitable for

1 piece INT-1 is standard supplied with a ball-joint



QUATRO-FIX 4 & 5



Ref.	QFIX-4	
Max. mounting range in mm.	345 x 280 mm.	
Max. load	30 kg	Max. 30
Suitable for	large projector situations	
Ref.	QFIX-5	
Mounting range in mm.	min. 268 x 243 - max. 430 x 360	
Max. load	30 kg	Max. 30
Suitable for	large projector situations	

BJ-PRO-INT1

BJ-PRO-INT2 100 x 100 mm.

90 x 90 mm.

QUATRO-FIX 6 & 7



Ref.	QFIX-6	
Mounting range in mm.	min. 200 x 85 - max. 410 x 475	
Max. load	80 kg	Max. 80
Suitable for	large projector situations	
Ref.	QFIX-7	
Max. mounting range in mm.	200 x 85 - 620 - 735	
Max. load	80 kg	Max. 80
Suitable for	large projector situations	

large projector situations



Short throw wall mounts

for projectors

The Audipack short throw wall mounts

are ideal to mount your projector directly on the wall or to an Audipack projection set up.





Easy installation with Audipack

wall mounts



Audipack short throw wall mounts with universal projector mount is a most flexible yet durable solution.

Audipack short throw wall mounts have slim dimensions, a modern design and provide 100% tolerance free projector mounting. The easily accessible hidden cable ducts are ideal for hiding projector cabling and routing it to the wall.

The projector is mounted onto the famous Audipack Quatrofix, with a ball joint that allows for a rigid, steady projector mounting.

The short throw mount can be easily attached directly to the wall or onto a frame, whichever is the best solution for the projection screen.

- Easy installation
- Rigid wall mounting
- Accurate projector adjustment
- Universal or brand related projector mounts

SHORT THROW ARMS



Ref.	PWM-ST0600	
Adjustment range in mm	360-600	Max. 20
Max. mounting range in mm	440 in diameter	
Ref.	PWM-ST1200	
Adjustment range in mm	960-1200	Max. 20
Max. mounting range in mm	440 in diameter	
Ref.	PWM-ST0800T	
Adjustment range in mm	500-800	20 Nax.
Max. mounting range in mm	440 in diameter	
Ref.	PWM-ST1500T	
Adjustment range in mm	800-1500	Max. 10
Max. mounting range in mm	440 in diameter	
Including Universal Quatro-Fix		

WALL MOUNT



Ref.	PWM-0450
Length in mm	450
See page for 123 for a projector mou	int, to mount your projector