

EK-600LU/EK-600LUL WUXGA Large Venue 3LCD Laser Projector



Totally NEW and Innovative LCD Laser Projector

Model		EK-600LU/600LUL			
Display Type		0.64" 3LCD			
Resolution		WUXGA (1920 x 1200)			
Aspect Ratio		16:10(Standard)/4:3(Compatible)			
Brightness		6,000 lm*			
Contrast Ratio		5,000,000:1			
Projection Light Source		Laser diode			
Light Source Life (Eco / Normal)		30,000 / 20,000 hrs			
Image Diagonal		30" - 300"			
Lens (F Value / Focal length)		F:1.5~2.08 / f=17.2~27.7mm			
Zoom Ratio		Manual x 1.6			
Throw Distance		0.76 – 12.88 m			
Throw Ratio		1.2~2.0 : 1			
Lens Shift		V + 60% (Manual)			
Keystone Correction		V: +/-30 degrees, H: +/-30 degrees Corner Correction Pincushion/Barrel Correction			
Scanning Frequency		H Sync: 15 -100 kHz, V sync: 24 - 85 Hz			
Dot Clock		300 MHz			
Input Signals - Computer		4K(3840 x 2160@30Hz, HDMI only) WUXGA(1920 x 1200) ~ VGA(640 x 480)			
Input Signals - Video		1080 i/p, 720 p, 576 i/p, 480 i/p			
	HDMI In	HDMI x 2			
	VGA In	Dsub15 x 1			
	HDBaseT In	x *1 (EK-600LUL is without HDBaseT)			
	Video In	RCA x 1			
Terminal	USB	USB Type A x 1 (Memory Viewer)			
	USB	USB Type B x 1 (Firmware)			
	VGA Out	Dsub15 x 1			
	Audio In	3.5mm MiniStereo x 1, RCA x 2			
	Audio Out	3.5mm MiniStereo x 1			
Fan Noise (Eco / Normal)		28 / 37 dB			
Dimensions (W x H x D)		390 x 128 x 294 mm			
Weight		5.2kg			
Power Requirements		AC 100 - 240 V, 50/60 Hz			
Power Consumption (Eco / Normal)		280W / 170W			
Thermal Dissipation		955 BTU			
Standard Accessories		AC Power Cord x 1 VGA cable x 1, Remote Control (with 2 x AAA Batteries) Quick Start Guide, Safety Guide			

*Center Lumens

*EK-600LUL is without HDBaseT

*Specifications is subject to change without notice

6,000 Lumens* WUXGA (1920 x 1200)

The EK-600LU and EK-600LUL, these new projectors are our latest LCD projector with laser light source in EIKI's Large venue projector product line.

The EK-600LU and 600LUL realize both quiet operation and high brightness by newly developed cooling system for optical engine.

The cooling system that is a sealed box that protects optical engine from dusts and filter-less design, provides higher cooling performance and lower fan noise.

In addition, this model offers the excellent projection image by the combination of 3LCD and Laser light source.

Moreover, it also provides variety of installation capability that is supported by friendly keystone adjustment enables to install at various places such as conference rooms, house of worships, museums and so on.

Key Features

- · Designed For Heavy-duty use
- · Long Life Time Laser Light Source
- · Side Change Filter
- · Quickly Power Off
- Advanced Anti-Theft Feature
- Auto Function
 - Auto Search
 - Auto Sync
 - Auto Ceiling and Auto Keystone
 - Five Picture Modes
 - Dynamic
 - Standard
 - Cinema
 - Blackboard
 - Color board
- · Built-In 16W Speaker
- Digital Zoom Adjustment
- Manual Lens Shift function(Vertical Only)

EK-600LU/EK-600LUL

WUXGA Large Venue 3LCD laser Projector

Dimensions

Terminals

Throw Distance

EIKI JAPAN Co., LTD 661-0953 Hyogo Amagasaki Higashisonoda 4-162-1-202



Conc. In							
Screen size	30"	100"	150"	200"	300"		
(WxH)mm	664x374	2214x1245	3321x1868	4428x2491	6641x3736		
Maximum	786	2704	4075	5445	8186		
Minimum	1293	4392	6605	8818	13244		