

EK-700LU

Resolution: WUXGA (1920x1200)
 Aspect Ratio: (16 : 10)

Screen Dimensions.

| | | | | | | | | | | |
|----|-----|-----|-----|-----|-----|------|-----|-----|-----|------|
| H' | 1.3 | 1.8 | 2.5 | 3.8 | 5 | 6.3 | 7.5 | 8.8 | 10 | 13.3 |
| W' | 2.1 | 2.8 | 4.0 | 6.0 | 8.0 | 10.0 | 12 | 14 | 16 | 21.2 |
| D" | 30 | 40 | 57 | 85 | 113 | 142 | 170 | 198 | 226 | 300 |

| EIKI Part No. | Diagonal | T/W | Shift Range | Throw Distance to Screen in feet. | | | | | | | | | |
|---------------|----------|------|-------------|-----------------------------------|-----|-----|------|------|------|------|------|------|------|
| EK-700LU | 30" | 1.22 | V: + 60% | 2.6 | 3.4 | 4.9 | 7.3 | 9.8 | 12.2 | 14.7 | 17.1 | 19.6 | 26.0 |
| | 300" | 1.98 | H: +/- 29% | 4.2 | 5.6 | 7.9 | 11.9 | 15.9 | 19.8 | 23.8 | 27.8 | 31.7 | 42.1 |

How to use the T/W column. If your screen size does not appear on this chart, use the T/W column to find the lens you need. Divide the Throw distance by the screen Width to get your "target T/W number". Then, look for a lens with a T/W range that covers it.

Calculations are from the front glass of the lens and accurate to approximately +/- 5%. Specifications are subject to change without notice.

Eiki International, Inc. Tel: 800-322-3454, E-mail: usa@eiki.com
 Website: <http://www.eiki.com>